



SPECIFICATIONS

Items	Specifications
Stand	Sturdy & Robert stand with anti-rust materials. Extended base with hand rests for enhanced and comfort.
Viewing Body	Binocular tube 45° inclined, 360° rotatable, Interpupillary distance adjustable 54-74mm. Vacuum coated Prism for better transmission and anti-fungus character.
Eyepiece	Wide Field focusable paired eyepiece WF10x/18mm, with foldable eye guard, lockable, anti-fungus coating
Nosepiece	Quadruple nosepiece (Ball bearing type) with rubber grip. PAR-CENTERED & PAR-FOCAL on CNC Machines.
Objectives	LP series DIN Semi-Plan Achromatic objectives 4x, 10x, 40x (spring loaded), 100x Oil (spring loaded) anti-fungus coating.
Mechanical Stage	Mechanical stage 135x125mm with Co-axial drive, highly smooth on ball slides, stainless steel holder for slide movement X-Y = 75mm x 50mm.
Condenser	Sub-stage abbe condenser NA 1.25 with aspheric lens. Iris diaphragm with snap-in blue filter. Rack and pinion movements on metal guide.
Focusing	Co-axial coarse and fine focusing on ball drive system for smooth movement with adjustable Tension Control knob.
Illumination	Halogen 6V-20W illumination with variable illumination control.
Electrical	Input 200v-240v AC - with removable imported cord.
Packing	PACKED in Styrofoam box, with operation manual, dust cover, cleaning cloth, power cord.
Optional Accessories	Dark Field attachment(Wet Condenser), Simple Polarising attachment.



Marketed by: Superfit Continental Pvt. Ltd.

5/6 Old Sitaram Building, First Floor, 204 Princess Street,
Mumbai 400002 INDIA Contact : +91-22-22018954 | 22054361
Email:- info@superfitindia.com, Website : www.superfitindia.com