



SPECIFICATIONS

Items	Specifications
Stand	Sturdy stand anti rust materials. Extended base
Viewing Body	Binocular tube 45° inclined, 360° rotatable
Eyepiece	Wide field eyepiece WF10x/18mm, with foldable eye guard, anti-fungus coating - locked in ocular tube
Nosepiece	Quadruple nosepiece (Ball bearing type).
Objectives	DIN Semi-Plan Achromatic objectives 4x,10x, 40x (spring loaded), 100x Oil (spring loaded) anti-fungus coating. PAR-CENTERED & PAR-FOCAL
Mechanical Stage	Mechanical stage with Co-axial drive, highly smooth on ball slides, stainless steel holder for slide movement X-Y = 75mm x 50mm.
Focusing	Co-axial coarse and fine focusing on ball drive system for smooth movement with Tension adjustable control knob.
Illumination	LED illumination, variable intensity control with illuminated ON/OFF switch, rechargeable battery. Up to 50,000 hours of LED life.
Electrical	Input 200v-240v AC through external power adapter for battery charging. Lithium - Ion rechargeable battery built-in.
Packing	PACKED in Styrofoam box, with operation manual, dust cover, cleaning cloth, power cord.



Marketed by: Superfit Continental Pvt. Ltd.

5/6 Old Sitaram Building, First Floor, 204 Princess Street,
Mumbai 400002 INDIA Contact : +91-22-22018954 | 22054361
Email:- info@superfitindia.com, Website : www.superfitindia.com